

GravelHold

TECHNICAL DATASHEET

DESCRIPTION

GravelHold is an environmentally friendly air-drying bonding solution that can be applied to both new and existing gravel up to 20mm in diameter to create solid, decorative surfaces within landscaped areas.

Application

Before application ensure that the substrate is clean and dry, with no rain forecast.

GravelHold is best applied through mixing with the gravel and laying with a trowel but can be also applied by pouring over the area via a watering can or drilling holes in the lid.

Do not let the binder pool in crevices, as this will extend the drying time.

Apply the binder sparingly to just 'wet out' the surface. Apply up to 3 coats if necessary.

GravelHold dries clear.

Application Rate will vary depending on the type of surface and the size of the aggregate, but we advise the following: 1ltr per m² per coat is typical.

Do not lay in direct sunlight. For best results lay at ambient temperatures 5°C-25°C.

Storage and Shelf Life Safety Information

Store out of direct sunlight in a humidity-controlled atmosphere, at 5-25°C. Avoid frost. Shelf life is 12 months from date of manufacture.

Safety Information

GravelHold has been classified as a non-hazardous substance but users are encouraged to refer to the Material Safety Data Sheet corresponding to this product. Precautions should be taken to ensure that gloves and safety glasses are worn when handling this product.

PROPERTY	VALUE	UNIT OF MEASURE
Appearance	Liquid	N/A
Colour	Off-White	N/A
Viscosity	12-19	cSt
pH Value	7.0 - 9.0	N/A

FOR INSTALLATION
INSTRUCTIONS, DOWNLOADS,
VIDEOS OR FURTHER GUIDANCE
VISIT

GCLPRODUCTS.CO.UK

GCL Products Ltd

Sheepbridge Lane
Chesterfield
Derbyshire
S41 9RX

